

PART NUMBER:**PANEL NUMBER:****JOB NAME:**

Page 1 of 2

ServiceTrack[®] ST 120

SYSTEM FEATURES



- Providing the highest level of protection with the lowest let-through voltage in the industry
- Fail-Safe Design
- Optional Component Level Fusing
- Single pulse tested at independent 3rd party lab
- Form C dry relay contacts and audible alarm with silence button
- Two suppression technologies: MOV and all mode Enhanced Transient Filter
- UL 1283 Tracking Filter
- Ultra, Compact Footprint – efficiency and performance
- 30-Year Unlimited Free Replacement Warranty
- Weatherproof Nema 4 steel enclosure

PRODUCT SPECIFICATIONS

GENERAL SPECIFICATIONS

Maximum Rated Surge Current: 120kA per phase; 60kA per mode

Application: ANSI/IEEE C62.41 Location C, B & A. Ideal for distribution panels, branch panels and critical loads

Design: Optimum performing parallel hybrid with component level fusing

Warranty: 30-Year Unlimited Free Replacement

Safety Listing: UL 1449 4th Ed., Type 1 for Type 1 & Type 2 locations and UL 1283

✓ RoHS Compliant

ELECTRICAL SPECIFICATIONS

Modes of Protection: All Modes: L-N, L-L, L-G, & N-G

Input Power Frequency: 40-440Hz (47-64 Hz with enhanced filter option)

Response Time: < 1 nanosecond

Standard Monitoring: Status indicator lights (one per phase & one service LED); Form C dry relay contacts for suppressor status; Audible alarm with silence button

Short Circuit Current Rating: 200 kAIC on all units.

No upstream over-current protection required on CLF unit.

Non CLF units require 60A Max fuse or breaker.

MECHANICAL SPECIFICATIONS

Dimensions (approx.): 11.50"H x 8.28"W x 6.28"D

(292 mm H x 210 mm W x 160 mm D)

Enclosure: Steel, Weatherproof. NEMA 4 (IP 56)

Connection: Hardwired via internal lugs #10 AWG-#2 AWG (5.26 mm2 - 26.7 mm2)

"-R" models come with #10 AWG leads

Mounting: Multi-point mounting feet

Operating Environment: -40° C to 70° C (-40° F to 160° F)

5% to 95% non-condensing humidity

Weight: 24 lbs. (10.9 kg)

Weight: 24 lbs. (10.9 kg)

AVAILABLE CONFIGURATIONS

Model Number	Description
TK-ST120-1P120	120VAC, 1ø 2-wire + grd
TK-ST120-1P240	240-277V, 1ø 2-wire + grd
TK-ST120-1S240	120/240VAC, 1ø SPLIT-PHASE, 3-wire + grd
TK-ST120-3Y208	120/208VAC, 3ø WYE, 4-wire + grd
TK-ST120-3Y380	220/380VAC, 3ø WYE, 4-wire + grd
TK-ST120-3Y400	230/400VAC, 3ø WYE, 4-wire + grd
TK-ST120-3Y415	240/415VAC, 3ø WYE, 4-wire + grd
TK-ST120-3Y480	277/480VAC, 3ø WYE, 4-wire + grd
TK-ST120-3Y600	347/600VAC, 3ø WYE, 4-wire + grd
TK-ST120-3D240	120/240VAC, 3ø high-leg DELTA, 4-wire + grd (B phase must be 208V)
TK-ST120-240NN	240VAC, 3ø DELTA, 3-wire + grd
TK-ST120-380NN	380VAC, 3ø DELTA, 3 wire + grd
TK-ST120-480NN	480VAC, 3ø DELTA, 3-wire + grd
TK-ST120-600NN	600VAC, 3ø DELTA, 3-wire + grd

AVAILABLE OPTIONS *Order as a Suffix Example: TK-ST120-3Y208-FL*

- Enhanced Transient Filter (ETF): add suffix "-F"
- Component Level Fusing (CLF): add suffix "-L"
- Surge Counter: add suffix "-B"
- NEMA 4X Stainless Steel Enclosure: add suffix "-XX"
- Recessable model 4.28" deep: add suffix "-R"

- ST-FMP-120/160 (for Flush-Mount Plate Kit)

- Non-Fused Disconnect Switch:

DN-200KAIC-60A-3/4 (for Nema 4 steel)

DN-200KAIC-60A-XX-3/4 (for Nema 4 stainless steel)

EMI / RFI FILTER ATTENUATION – MIL STANDARD 220B



Frequency	Attenuation
1kHz	2 dB
10kHz	17 dB
100kHz	40 dB
1MHz	18 dB
10MHz	6 dB
100MHz	1 dB
Max. Attenuation Frequency	41 dB @ 106 kHz

Made in U.S.A.

Page 1 of 2



ServiceTrack® ST 120



Model Number	System Voltage	System Configuration	Protection Mode	ANSI/IEEE C62.41.1-2002, C62.41.2-2002, & C62.45-2002 Measured Limited Voltage				UL Voltage Ratings UL 1449 2 nd Edition/ Voltage Protection Ratings		
				MCOV	ETF Models A1 Ring Wave 2kV, 67A 180° Phase Angle		All Models B3/C1 Impulse Wave 6kV, 3kA 90° Phase Angle		All Models C3 Impulse Wave 20kV, 10kA 90° Phase Angle	
					40V	60V	651V			978V
TK-ST120-1P120	120V	1-Phase 2-wire+grnd	L-N	150V	40V	651V	960V	400/700		
			L-G	150V	76V	640V	1010V	400/700		
			N-G	150V	54V	646V	860V	400/700		
TK-ST120-1P240	240-277V	1-Phase 2-wire+grnd	L-N	320V	42V	978V	1437V	800/1000		
			L-G	320V	61V	969V	1523V	800/1000		
			N-G	320V	50V	979V	1340V	800/1000		
TK-ST120-1S240	120/240V	1-Phase 3-wire+grnd	L-N	150V	40V	651V	960V	400/700		
			L-G	150V	76V	640V	1010V	400/700		
			L-L	300V	46V	1041V	1310V	800/1200		
TK-ST120-3Y208	120/208V	3-Phase WYE 4-wire+grnd	N-G	150V	54V	646V	860V	400/700		
			L-N	150V	40V	651V	960V	400/700		
			L-G	150V	76V	640V	1010V	400/700		
TK-ST120-3Y208	120/208V	3-Phase WYE 4-wire+grnd	L-L	300V	46V	1041V	1310V	800/1200		
			N-G	150V	54V	646V	860V	400/700		
			L-N	150V	40V	651V	960V	400/700		
TK-ST120-3Y380	220/380V	3-Phase WYE 4-wire+grnd	L-G	150V	76V	640V	1010V	400/700		
			L-L	640V	60V	1792V	2190V	1500/1800		
			N-G	320V	50V	967V	1340V	800/1000		
TK-ST120-3Y400	230/400V	3-Phase WYE 4-wire+grnd	L-N	320V	42V	968V	1437V	800/1000		
			L-G	320V	61V	979V	1523V	800/1000		
			L-L	640V	60V	1792V	2190V	1500/1800		
TK-ST120-3Y415	240/415V	3-Phase WYE 4-wire+grnd	N-G	320V	50V	967V	1340V	800/1000		
			L-N	320V	42V	968V	1437V	800/1000		
			L-G	320V	61V	979V	1523V	800/1000		
TK-ST120-3Y480	277/480V	3-Phase WYE 4-wire+grnd	L-L	640V	60V	1792V	2190V	1500/1800		
			N-G	320V	50V	967V	1340V	800/1000		
			L-N	420V	56V	1295V	1710V	1200/1500		
TK-ST120-3Y600	347/600V	3-Phase WYE 4-wire+grnd	L-G	420V	99V	1295V	1783V	1200/1500		
			L-L	840V	76V	2130V	2893V	2000/2500		
			N-G	420V	88V	1292V	1610V	1200/1500		
TK-ST120-3Y600	347/600V	3-Phase WYE 4-wire+grnd	L-N	150V	40V	654V	960V	400/700		
			H-N	320V	42V	984V	1437V	800/1000		
			L-G	150V	76V	645V	1010V	400/700		
TK-ST120-3D240	120/240V	3-Phase high-leg DELTA 4-wire+grnd	H-G	320V	61V	988V	1523V	800/1000		
			L-L	320V	46V	1044V	1310V	800/1000		
			H-L	470V	46V	1250V	1640V	1500/1500		
TK-ST120-3D240	120/240V	3-Phase high-leg DELTA 4-wire+grnd	N-G	150V	54V	654V	860V	400/700		
			L-N	320V	42V	984V	1437V	800/1000		
			L-L	320V	31V	981V	1303V	800/1000		
TK-ST120-240NN	240V	3-Phase DELTA 3-wire+grnd	L-G	320V	565V	980V	1150V	800/1000		
TK-ST120-240NN	240V	3-Phase DELTA 3-wire+grnd	L-L	320V	31V	981V	1303V	800/1000		
			L-G	550V	912V	1689V	1870V	1500/1800		
TK-ST120-380NN	380V	3-Phase DELTA 3-wire+grnd	L-L	550V	39V	1697V	1950V	1500/1800		
			L-G	550V	912V	1689V	1870V	1500/1800		
TK-ST120-480NN	480V	3-Phase DELTA 3-wire+grnd	L-L	550V	39V	1697V	1950V	1500/1800		
			L-G	550V	912V	1689V	1870V	1500/1800		
TK-ST120-600NN	600V	3-Phase DELTA 3-wire+grnd	L-G	750V	1253V	2202V	2420V	2000/2500		
			L-L	750V	36V	2217V	2410V	2000/2500		

ETF = Enhanced Transient Filter (-F suffix). All tests performed with 6" (152 mm) lead length, positive polarity. All voltages are peak values (±10%) measured from the zero reference point at the phase angles referenced above using a 10 µs/div display rate and 500 Mega samples/sec sampling rate.